

DISC CULTIVATOR ONTARIO

- Extended distance between the first and second row of discs
- Increased ground clearance under the frame
- Improved clearance of crop residues
- Discs mounted on high-strength double tines
- Standard disc diameter 510 mm, can be replaced by a larger diameter of 560 mm
- Integrated axle for even load and better manoeuvrability
- Suitable for shallow full-range undercut, cultivating and intensive mixing of crop residues up to a depth of 12 cm
- Wide range of support rollers. e.g. double U-rollers
- Robust frame made of high-strength materials



Type
semi-carried,
hydraulically folded



Working range
5 - 6 m



Working speed
až 15 km/h



Working depth
až 12 cm



Diameter of discs
510 mm
(optional 560 mm)



Application
shallow tillage,
pre-sowing preparation



EU homologation

TECHNICAL DATA		500	600
Working width	[m]	5	6
Transport width	[m]	2,95	2,95
Number of disks	[ks]	40	48
Max. working depth	[cm]	12	12
Max. working speed	[km/h]	15	15
Frame		Two-piece, semi-carried, hydraulically folded	
Minimum tractor power	[kW/HP]	140/180	170/230
Hinge (standard)		cat. 3	cat. 3
Wheels (standard)		19/45-17	19/45-17

WWW.SMSCZ.CZ

SMS CZ s. r. o. / U Saské brány 12, Rokycany, 337 01 / smscz@smscz.cz / +420 371 722 137

@smscz.machinery

@smscz_machinery



Funded by
the European Union