

NEW 2024



ADVANTAGES OF THE MACHINE

- It can combine up to 7 working operations in one pass, saving time, operating costs and other machinery, as well as saving the soil from negative compaction due to repeated driving on the land
- The wide spacing of the individual working sections prevents clogging, so the machine can be used in wet conditions as well as on soils with a small proportion of crop residues
- The four-part frame with free suspension of the individual sections allows excellent ground following
- Hydraulically folded machine into forward transport position, in working position the transport wheels are placed in front of the working sections

- High working performance even at maximum working speeds of up to 15 km/h
- Wide range of accessories from rollers, tines sections, track cultivator, hydraulic depth adjustment, etc.
- Low maintenance with minimum lubrication points

APPLICATION

- Land levelling, lump crushing and precise seedbed preparation
- Shallow subsoil on soils with minimal plant residues
- Suitable wherever high daily outputs are required



Type

semi-carried, hydraulically folded



Working width

12 m



Working speed

up to 15 km/h



Application

Pre-sowing preparation



EU homologation

TECHNICAL DATA

1200

Working width	cm	1200
Transport width	cm	298
Weight	kg	10 000
Min. output	kW/HP	240/320
Number of working frame		4
Working speed	km/h	8-15
Linkage type		eye 51 mm
Tyre size		550/45-22,5

WWW.SMSCZ.CZ

SMS CZ s. r. o. | U Saské brány 12, Rokycany, 337 01 | smscz@smscz.cz | +420 371 722 137

@smscz.machinery

@smscz_machinery



Funded by
the European Union